

Page 2 of 13

Serial No.: 10/620,183 Confirmation No.: 8654 Filed: July 15, 2003

For: CATALYTIC PARTIAL OXIDATION OF HYDROCARBONS

Amendments to the Claims

This listing of claims replaces all prior versions, and listings, of claims in the aboveidentified application:

- 1. (Original) A process for the production of a compound comprising carbon, the process comprising providing a fuel source comprising at least one organic compound to a reactor, forming a film of the fuel source on a wall of the reactor, providing a source of oxygen comprising molecular oxygen to the reactor, contacting the fuel source with the source of oxygen, forming a vaporized mixture of fuel and oxygen, then contacting the vaporized mixture of fuel and oxygen with a catalyst under conditions effective to produce a reaction product comprising a carbon containing compound.
- 2. (Original) The process of claim 1 wherein the process is carried out under autothermal conditions.
- 3. (Original) The process of claim 1 wherein the vaporized mixture of fuel and oxygen contacts the catalyst for at least about 5 milliseconds.
- 4. (Original) The process of claim 3 wherein the vaporized mixture of fuel and oxygen contacts the catalyst for no greater than about 25 milliseconds.
- 5. (Original) The process of claim 1 wherein the organic compound is a liquid hydrocarbon with at least 6 carbon atoms.
- 6. (Original) The process of claim 5 wherein the liquid hydrocarbon is a C_6 - C_{30} hydrocarbon.







Page 3 of 13

Serial No.: 10/620,183 Confirmation No.: 8654 Filed: July 15, 2003

- 7. (Original) The process of claim 1 wherein the process is carried out without adding water.
- 8. (Original) The process of claim 1 wherein the catalyst comprises a metal selected from the group consisting of a Group VIII metal, a Group IB metal, tin, and combinations thereof.
- 9. (Original) The process of claim 8 wherein the metal comprises rhodium.
- 10. (Original) The process of claim 1 wherein the source of oxygen comprises air.
- 11. (Original) The process of claim 1 further comprising contacting the fuel source and source of oxygen with water.
- 12. (Original) A process for the production of an alkene, the process comprising:

 providing a fuel source comprising at least one liquid hydrocarbon;

 providing at least one source of oxygen comprising molecular oxygen;

 delivering the fuel source to a reactor comprising a wall;

 forming a film of the fuel source on the reactor wall;

 contacting the fuel source with the source of oxygen;

 forming a vaporized mixture of fuel and oxygen; and

 contacting the vaporized mixture of fuel and oxygen with a catalyst under conditions

 effective to produce a reaction product comprising an alkene.
- 13. (Original) The process of claim 12 wherein the process is carried out under autothermal conditions.
- 14. (Original) The process of claim 12 wherein the vaporized mixture of fuel and oxygen contacts the catalyst for at least about 5 milliseconds.







Page 4 of 13

Amendment and Response Under 37 C.F.R. §1.116 - Expedited Examining Procedure

Serial No.: 10/620,183 Confirmation No.: 8654 Filed: July 15, 2003

- 15. (Original) The process of claim 14 wherein the vaporized mixture of fuel and oxygen contacts the catalyst for no greater than about 25 milliseconds.
- 16. (Original) The process of claim 12 wherein the liquid hydrocarbon comprises at least 6 carbon atoms.
- 17. (Original) The process of claim 12 wherein the alkene is ethylene.
- 18. (Previously Presented) The process of claim 17 wherein at least about 35 percent of the fuel source that is reacted forms ethylene.
- 19. (Original) The process of claim 12 wherein the alkene is propylene.
- 20. (Original) The process of claim 19 wherein at least about 15 percent of the fuel source that is reacted forms propylene.
- 21. (Original) The process of claim 20 wherein no greater than about 50 percent of the fuel source that is reacted forms propylene.
- 22. (Original) The process of claim 12 wherein the catalyst comprises a metal disposed on a support, wherein the metal is selected from the group consisting of a Group VIII metal, a Group IB metal, tin, and combinations thereof.
- 23. (Original) The process of claim 22 wherein the metal is selected from the group consisting of rhodium, platinum, and mixtures thereof.
- 24. (Original) The process of claim 23 wherein the catalyst further comprises tin.
- 25. (Original) The process of claim 22 wherein the support is a ceramic foam monolith.





Page 5 of 13

Serial No.: 10/620,183 Confirmation No.: 8654 Filed: July 15, 2003

- 26. (Original) The process of claim 12 wherein carbon is present in the fuel source in an atomic ratio of at least about 0.8:1 carbon to oxygen.
- 27. (Original) The process of claim 6 wherein carbon is present in the fuel source in an atomic ratio of no greater than about 5:1 carbon to oxygen.
- 28. (Original) The process of claim 12 wherein the source of oxygen comprises air.
- 29. (Original) The process of claim 12 wherein the source of oxygen is pure O₂.
- 30. (Original) The process of claim 12 further comprising contacting the fuel source and source of oxygen with water.
- 31. (Original) The process of claim 12 wherein the vaporized mixture of fuel and oxygen contacts the catalyst at a flow rate of at least about 0.5 standard liters per minute.
- 32. (Original) The process of claim 31 wherein vaporized mixture of fuel and oxygen contacts the catalyst at a flow rate of no greater than about 20 standard liters per minute.
- 33. (Original) The process of claim 12 wherein the fuel source and the source of oxygen are vaporized and mixed substantially simultaneously.
- 34. (Original) The process of claim 33 wherein the mixture of fuel and oxygen is heated to a temperature of at least about 25°C above the boiling point of the fuel source prior to contacting the catalyst.
- 35. (Original) The process of claim 34 wherein the fuel source and the source of oxygen are heated to a temperature of no greater than about 150°C above the boiling point of the fuel source prior to contacting the catalyst.



Page 6 of 13

Serial No.: 10/620,183 Confirmation No.: 8654 Filed: July 15, 2003

- 36. (Original) A process for the production of an α-olefin, the process comprising: providing a fuel source comprising at least one liquid n-alkane; providing at least one source of oxygen comprising molecular oxygen; delivering the fuel source to a reactor comprising a wall; forming a film of the fuel source on the reactor wall; contacting the fuel source with the source of oxygen; forming a vaporized mixture of fuel and oxygen; and contacting the vaporized mixture of fuel and oxygen with a catalyst under conditions effective to produce a reaction product comprising an α-olefin.
- 37. (Original) The process of claim 36 wherein the process is carried out under autothermal conditions.
- 38. (Original) The process of claim 36 wherein the vaporized mixture of fuel and oxygen contacts the catalyst for at least about 5 milliseconds.
- 39. (Original) The process of claim 38 wherein the vaporized mixture of fuel and oxygen contacts the catalyst for no greater than about 25 milliseconds.
- 40. (Original) The process of claim 36 wherein the *n*-alkane comprises at least 6 carbon atoms.
- 41. (Original) The process of claim 36 wherein at least about 20 percent of the fuel source that is reacted forms an α -olefin.
- 42. (Original) The process of claim 41 wherein about 100 percent of the fuel source that is reacted forms an α -olefin.



Page 7 of 13

Serial No.: 10/620,183 Confirmation No.: 8654

Confirmation No.: 8654 Filed: July 15, 2003

- 43. (Previously Presented) The process of claim 36 wherein the catalyst comprises a metal disposed on a support, wherein the metal is selected from the group consisting of a Group VIII metal, a Group IB metal, tin, and combinations thereof.
- 44. (Original) The process of claim 43 wherein the metal is selected from the group consisting of rhodium, platinum, and mixtures thereof.
- 45. (Original) The process of claim 44 wherein the catalyst further comprises tin.
- 46. (Original) The process of claim 43 wherein the support is a ceramic foam monolith.
- 47. (Original) The process of claim 36 wherein carbon is present in the fuel source in an atomic ratio of at least about 2:1 carbon to oxygen.
- 48. (Original) The process of claim 47 wherein carbon is present in the fuel source in an atomic ratio of no greater than about 10:1 carbon atom to oxygen atom.
- 49. (Original) The process of claim 36 wherein the source of oxygen comprises air.
- 50. (Original) The process of claim 36 wherein the source of oxygen is pure O_2 .
- 51. (Original) The process of claim 36 further comprising contacting the fuel source and the source of oxygen with water.
- 52. (Original) The process of claim 36 wherein the vaporized mixture of fuel and oxygen contacts the catalyst at a flow rate of at least about 0.5 standard liters per minute.
- 53. (Original) The process of claim 52 wherein the vaporized mixture of fuel and oxygen contacts the catalyst at a flow rate of no greater than about 20 standard liters per minute.

Amendment and Response Under 37 C.F.R. §1.116 - Expedited Examining Procedure

Page 8 of 13

Serial No.: 10/620,183 Confirmation No.: 8654 Filed: July 15, 2003

For CATALYTIC PARTIAL OXIDATION OF HYDROCARBONS

- 54. (Original) The process of claim 36 wherein the fuel source and the source of oxygen are vaporized and mixed substantially simultaneously.
- 55. (Original) The process of claim 54 wherein the mixture of fuel and oxygen are heated to a temperature of at least about 25°C above the boiling point of the fuel source prior to contacting the catalyst.
- 56. (Original) The process of claim 55 wherein the fuel source and the source of oxygen are heated to a temperature of no greater than about 150°C above the boiling point of the fuel source prior to contacting the catalyst.

57-75. (Canceled)

- 76. (Currently Amended) A process for the production of a compound comprising carbon, the process comprising feeding a liquid fuel source comprising at least one organic compound to a reactor comprising at least one wall, wherein the wall of the reactor has been preheated to a temperature of from about 250°C to about 400°C, providing a source of oxygen comprising molecular oxygen to the reactor, contacting the fuel source with the source of oxygen, forming a vaporized mixture of fuel and oxygen, then contacting the vaporized mixture of fuel and oxygen with a catalyst under conditions effective to produce a reaction product comprising a carbon containing compound.
- 77. (Currently Amended) A process for the production of an alkene, the process comprising: providing a liquid fuel source comprising at least one hydrocarbon; providing at least one source of oxygen comprising molecular oxygen; feeding the liquid fuel source to a wall of a reactor; contacting the liquid fuel source with the source of oxygen; forming a vaporized mixture of fuel and oxygen; and

Page 9 of 13

Serial No.: 10/620,183 Confirmation No.: 8654 Filed: July 15, 2003

For: CATALYTIC PARTIAL OXIDATION OF HYDROCARBONS

effective to produce a reaction product comprising an α -olefin.

contacting the vaporized mixture of fuel and oxygen with a catalyst under conditions effective to produce a reaction product comprising an alkene.

(Previously Presented) A process for the production of an α-olefin, the process comprising:
providing a liquid fuel source comprising at least one n-alkane;
providing at least one source of oxygen comprising molecular oxygen;
feeding the liquid fuel source to a wall of a reactor;
contacting the liquid fuel source with the source of oxygen;
forming a vaporized mixture of fuel and oxygen; and
contacting the vaporized mixture of fuel and oxygen with a catalyst under conditions

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:
BLACK BORDERS
☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
☐ FADED TEXT OR DRAWING
☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
☐ SKEWED/SLANTED IMAGES
☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
☐ GRAY SCALE DOCUMENTS
☐ LINES OR MARKS ON ORIGINAL DOCUMENT
☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
П отнер.

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.